



MARKING

S2
IHI
2-14
CU9AL
UL LOGO
CSA LOGO

FOR FURTHER INFORMATION ON THE PROPER USE OF THIS PRODUCT IN SPECIFIC APPLICATIONS SEE
<http://www.ihiconnectors.com/GuideToFlexFlexibleFineStrandedWireCableMechanicalLugsFAQ.html>

FLEX WIRE 4-12 AWG
 4-16 AWG with FERRULE

<http://www.ihiconnectors.com/Technical-Data-Installation.htm>

LISTED ZMVV POWER LUG RATED UL486A-B FOR (6) 2-14 AWG
 WIRES AT 90C RATINGS UL LISTED AND CSA CERTIFIED. MOUNTING
 USING TWO (2) #10 (OR m5) BOLTS & WASHERS
 THE CENTER MOUNTING HOLE IS OPTIONAL & MAY BE USED FOR
 OTHER PURPOSES RELATED TO SPECIFIC APPLICATION.



Expanded wire range with use of ferrules.
 TORK KRIMP®, self crimping of standard UL Listed ferrules protected by PATENT No.10630005
 PATENT: ihiconnectors.com/patent.html
 For full instructions: lugsdirect.com/PDF Documents/IHI Agency Labels/S2-AGENCY-LABEL.pdf

GENERAL TOLERANCES ±.015 [±.039MM]		IHI® CONNECTORS® INTERNATIONAL HYDRAULICS, INC.	
<small>COPYRIGHT (per latest date) of International Hydraulics, Inc. (IHI®). ALL RIGHTS RESERVED. This complete engineering drawing, schematics, and design are proprietary and confidential property of International Hydraulics, Inc. (IHI®) in Cleveland, Ohio, and may not be duplicated, used for the basis of design or manufacture without prior written permission of its owner. Contents contain a combination of registered trademark, copyright, or patent protections exclusively owned by IHI® which are not to be infringed upon. NOT FOR USE WHERE FAILURE CREATES A HAZARD TO HUMAN HEALTH OR SAFETY. All products are subject to this full disclaimer: ihiconnectors.com/disclaimer.html</small>		DESCRIPTION	
UNCONTROLLED COPY IF PRINTED		(6) 2-14 AWG STACK LUG	
		6S2-STK-21-19	
THIRD ANGLE PROJECTION	SIZE A	MATERIAL 6061-T6	PROCESS/FINISH TIN PLATED
DRAWN BY cridley	DATE 7/7/2018	DWG NO. 6S2-STK-21-19(SALES)	SHEET 1:1
			REV 0