

IHI Connectors

International Hydraulics Inc.
ihconnectors.com ©



200116



Listed 84JM
ZMVV
E129884

Pressure Terminal
Connectors

NRTL Cat. No.
2S2/0

2/0-14 CU9AL 90°C



ihconnectors.com/striplength

(#)



ihconnectors.com/flex

(#) FLEX - covers stranding classes within G, H, I/DLO, Metric class5 and K/MTW. (##) mm2 sizes within AWG/kcmil ranges are included.
PARALLELING: Rated for PAIRS of wires.

LABEL 1 OF 2

Wire Size Copper (solid to semi-rigid stranded and metric mm ² , ##)	Rating °C	All Torque in in.-lbs. For N-M divide by 8.85.		
		Wire Size FLEX Copper (#)	Wire Size aluminum	Torque (all drive means)
N/A	90°	1/0-1	N/A	75
N/A		1-4	N/A	55
2/0-3		4-8	2/0-3	50
4-6		8-10	4-6	45
8		10-14	8	40
10-14		N/A	10-12	35

LABEL 2 OF 2

All Torque in in.-lbs. For N-M divide by 8.85.

Wire Size Copper (solid to semi-rigid stranded and metric mm ² , ##)	Rating °C	Wire Size aluminum	Torque (all drive means)
2/0-14	75°	2/0-12	120@

IHI Connectors

International Hydraulics Inc.
ihconnectors.com ©



Listed 84JM
ZMVV, ZMVV7
E129884

(##) mm2 sizes within AWG/kcmil ranges are included.
PARALLELING: Rated for PAIRS of wires.
(@) When 120 in-lb torque is used, it shall use hex socket screw only.



ihconnectors.com/striplength

Pressure Terminal
Connectors
NRTL Cat. No.
2S2/0

2/0-14 CU7AL 75°C