

IHI Connectors

International Hydraulics Inc.
ihiconnectors.com ©



Pressure Terminal
Connectors

NRTL Cat. No.
S2/0

2/0-14 CU9AL 90°C

LABEL 1 OF 2

Wire Size Copper (solid to semi-rigid stranded and metric mm ² , ##)	All Torque in in-lbs. For N-M divide by 8.85.			
	Rating °C	Wire Size FLEX Copper(##)	Wire Size aluminum	Torque (all drive means)
N/A	90°	1/0-1	N/A	75
N/A		1-4	N/A	55
2/0-3		4-8	2/0-3	50
4-6		8-10	4-6	45
8		10-14	8	40
10-14		N/A	10-12	35



ihiconnectors.com/striplength

(#)



ihiconnectors.com/flex

(#) FLEX - covers stranding classes within G, H, I/DLO, Metric class5 and K/MTW. (##) mm² sizes within AWG/kcmil ranges are included.

LABEL 2 OF 2

IHI Connectors

International Hydraulics Inc.
ihiconnectors.com ©



Listed 84JM
ZMVV, ZMVV7
E129884

All Torque in in-lbs. For N-M divide by 8.85.

Wire Size Copper (solid to semi-rigid stranded and metric mm ² , ##)	Rating °C	Wire Size aluminum	Torque (all drive means)
2/0-14	75°	2/0-12	120@

(##) mm² sizes within AWG/kcmil ranges are included.
(@) When 120 in-lb torque is used, it shall use hex
socket screw only.



ihiconnectors.com/striplength

Pressure Terminal
Connectors

NRTL Cat. No.
S2/0

2/0-14 CU7AL 75°C