



200116



Listed 84JM  
ZMVV  
E129884

Pressure Terminal  
Connectors

NRTL Cat. No.

**S1/0**

1/0-14 AL9CU

90°

| Wire Size<br>Copper (solid to<br>semi-rigid stranded<br>and metric mm <sup>2</sup> , ##) | All Torque in in-lbs. For N-M divide by 8.85 |                       |                                |
|--|--|-----------------------|--------------------------------|
|  | Wire Size<br>FLEX Copper<br>(#)              | Wire Size<br>aluminum | Torque<br>(all drive<br>means) |
| N/A  | 1-3 AWG<br>25-35 mm <sup>2</sup>             | N/A                   | 55                             |
| 1/0-3 AWG<br>50-25 mm <sup>2</sup><br>(2) 4-6 AWG<br>(2) 16-10 mm <sup>2</sup>           | 4-6 AWG<br>16-10 mm <sup>2</sup>             | 1/0-3                 | 50                             |
| 4-6 AWG<br>16-10mm <sup>2</sup><br>(2) 8 AWG<br>(2) 6 mm <sup>2</sup>                    | 8 AWG  | 4-6                   | 45                             |
| 8 AWG, 6mm <sup>2</sup><br>(2)10-14 AWG  | N/A  | 8                     | 40                             |
| 10-14  | N/A  | 10-12                 | 35                             |

(#) FLEX - covers stranding classes within G, H, I/DLO,  
Metric class5 and K/MTW.(##) mm2 sizes within  
AWG/kcmil ranges are included.