



Listed 84JM  
ZMVV  
E129884



200116

Pressure Terminal  
Connectors

NRTL Cat. No.

**S4-3**

4-14 AL7CU | 75°

(#) FLEX - covers stranding classes within G, H, I/DLO, Metric class 5 and K/MTW. (##) mm<sup>2</sup> sizes within AWG/kcmil ranges are included.

(%) B, K includes flex wires classes B-K, and metric mm<sup>2</sup> class 2 & 5 in the rated gauge range

(+) Dual wire combinations must be the same wire gauge, stranding type, conductor material and insulation type (++) UL Listed ferrules are to be used according to the ferrule manufacturer's instructions. May be field or factory installed.

Wire Size <b>COPPER</b> (solid to semi-rigid stranded and metric mm <sup>2</sup> , ##, +, ++)	Wire Size <b>FLEX COPPER</b> (#, +, ++)	Wire Size <b>ALUMINUM</b>	Torque (all drive means)
4-6 AWG	N/A	4-6 AWG	35
(1) or (2) 8 AWG	N/A	(1) or (2) 8 AWG	25
(1) or (2) 10-14 AWG SOL, B, C	N/A	(1) 10-12 AWG	20
(1) or (2) 8 AWG	% B-K Single or twin ferrule	N/A	25
(1) or (2) 10-14 AWG Single or twin ferrule	% B-K Single or twin ferrule	N/A	20

All Torque in in-lbs. For N-M divide by 8.85.