



**MARKING: IHI, 2S2/0, UL, CU9AL, 2/0-14, CSA**

Part is mounted with customer supplied (2 sets) 1/4" minimum grade 2 bolts, nuts and (2) washers or (2 sets) M6 grade 8.8 bolts, nuts, and (2) washers, using the same typical tightening torque of 66in.-lbs or 7.5 N-M. Zinc plated, non lubricated hardware. M7 hardware sets may also be used.

NOT FOR USE WHERE FAILURE CREATES A HAZARD TO HUMAN HEALTH OR SAFETY. ALL PRODUCTS ARE SUBJECT TO THIS FULL DISCLAIMER: <http://www.ihiconnectors.com/disclaimer.html>

FOR FURTHER INFORMATION ON THE PROPER USE OF THIS PRODUCT IN SPECIFIC APPLICATIONS SEE <http://www.ihiconnectors.com/GuideToFlexFlexibleFineStrandedWireCableMechanicalLugsFAQ.html>

<http://www.ihiconnectors.com/Technical-Data-Installation.htm>

<small>THIS DRAWING AND DESIGN ARE THE PROPERTY OF INTERNATIONAL HYDRAULICS, INC., CLEVELAND, OHIO, AND MAY NOT BE DUPLICATED, USED FOR THE BASIS OF DESIGN OR MANUFACTURE WITHOUT THE WRITTEN PERMISSION OF INTERNATIONAL HYDRAULICS, INC., CLEVELAND, OHIO.</small>		<b>INTERNATIONAL HYDRAULICS, INC.</b>	
GENERAL TOLERANCES $\pm .015$ ( $\pm 0.038$ )		<b>TITLE:</b> <b>2S2/0-31-42</b> <b>CONNECTOR</b>	
<b>MATERIAL:</b> <b>6061-T6</b> <b>(1075)</b>	<b>SIZE:</b> <b>TDS</b>	<b>DRAWN BY:</b> <b>TDS</b>	<b>DWG NO.:</b> <b>2S2/0-31-42(SALES)</b>
<b>FINISH:</b> <b>TIN PLATE</b> <b>EMS</b>	<b>DATE:</b> <b>8/20/09</b>	<b>REV:</b> <b>1</b>	<b>THIS IS A CAD DRAWING, DO NOT MANUALLY REVISE</b>