



MARKING: IHI UL LOGO  
500-4 CU7AL



BOLT SIZE 1/2" GR. 2 M12 GR 8.8



NOT FOR USE WHERE FAILURE CREATES A HAZARD TO HUMAN HEALTH OR SAFETY. ALL PRODUCTS ARE SUBJECT TO THIS FULL DISCLAIMER: <http://www.ihconnectors.com/disclaimer.html>

FOR FURTHER INFORMATION ON THE PROPER USE OF THIS PRODUCT IN SPECIFIC APPLICATIONS SEE <http://www.ihconnectors.com/GuideToFlexFlexibleFineStrandedWireCableMechanicalLugsFAQ.html>

<http://www.ihconnectors.com/Technical-Data-Installation.htm>

IHI UL/CSA Installation Guide to Drill or Enlarge Mounting Holes:

<https://lugsdirect.com/PDF%20Documents/IHI-MTG-HOLE-FIELD-MODS-UL&CSA-CERTIFICATIONS.pdf>

Cat. No. 2S500 Style No. ALL

■ Drill, Enlarge, or Modify Mounting Holes

1) Increase hole(s) dia. to 1/2 bolt (.516 drill dia.)

2) Move location of mounting hole(s)

3) If buying blank lug, put custom hole(s) in.

EXTRUSION: X6293  
SCREWS: (2) 11941

<small>THIS DRAWING AND DESIGN ARE THE PROPERTY OF INTERNATIONAL HYDRAULICS, INC., CLEVELAND, OHIO, AND MAY NOT BE DUPLICATED, USED FOR THE BASIS OF DESIGN OR MANUFACTURE WITHOUT THE WRITTEN PERMISSION OF INTERNATIONAL HYDRAULICS, INC., CLEVELAND, OHIO.</small>					<b>INTERNATIONAL HYDRAULICS, INC.</b>				
<b>GENERAL TOLERANCES</b> $\pm .015$ ( $\pm 0,39$ )					TITLE: <b>DUAL 500kcmil LUG</b> <b>500kcmil-4 AWG B,C, FLEX</b>				
MATERIAL: 6061-T6		SIZE: A	DRAWN BY: cridley		DWG NO.: 2S500-53-63		REV: 0		
FINISH: TIN PLATE		DATE: 10-22-2016			<b>IHI CONNECTORS</b>				