


**REF. .50 MAX AFTER** 

PART MARKED AL7CU 4-14 P4

IHI Logo



SCREW INSERTION

Ø.25

1/16 SPACING
BETWEEN INDENTS

NOT FOR USE WHERE FAILURE CREATES A HAZARD TO HUMAN HEALTH OR SAFETY. ALL PRODUCTS ARE SUBJECT TO THIS FULL DISCLAIMER:

http://www.ihiconnectors.com/disclaimer.html

FOR FURTHER INFORMATION ON THE PROPER USE OF THIS PRODUCT IN SPECIFIC APPLICATIONS SEE

http://www.ihiconnectors.com/GuideToFlexFlexibleFineStrandedWireCableMechanicalLugsFAQ.html http://www.ihiconnectors.com/Technical-Data-Installation.htm

THIS DRAWING AND DESIGN ARE THE PROPERTY OF INTERNATIONAL HYDRAULICS, INC., QLEVELAND, CHIO, AND MAY NOT BE DUPLICATED,	INTERNATIONAL HYDRAULICS, INC.			
USED FOR THE BASIS OF DESIGN OR MANUFACTURE WITHOUT THE WRITTEN PERMISSION OF INTERNATIONAL HYDRALLICS, INC., CLEVELAND, OH C.	TITLE:	P4-HEX (SALES)		
GENERAL TOLERANCES ±.015 (±0,038)	CONNECTOR			
MATERIAL: 6061-T6 (17917)	SIZE:	DRAWN BY: TDS	DWG NO.: P4-HEX (SALES)	REV:
FINISH:TIN PLATE EMS	DATE: 01/26/09 4/21/15		IHI CONNECTORS	