



**NOTES:**

1. FINISH: TIN PLATE FOR SOLDERING
2. PART IS NOT UL/CSA LISTED/CERTIFIED (SEE PART B2A-PCB OR B12-PCB FOR LISTED PARTS) BUT IS CAPABLE OF PASSING UL686
3. FOR .06 PCB MIN. BOARD THICKNESS
4. USE ROUTED SLOT IN PCB FOR .140 FOOT, ALL FINAL PCB SPECS BASED ON BUYER TESTING AND APPROVAL
5. STANDARD PART HAS STAINLESS STEEL SCREW INSTALLED.
6. ACCEPTS COPPER OR ALUMINUM WIRE (SOLID OR STRANDED)

<small>THIS DRAWING AND DESIGN ARE THE PROPERTY OF INTERNATIONAL HYDRAULICS, INC., CLEVELAND, OHIO, AND MAY NOT BE DUPLICATED, USED FOR THE BASIS OF DESIGN OR MANUFACTURE WITHOUT THE WRITTEN PERMISSION OF INTERNATIONAL HYDRAULICS, INC., CLEVELAND, OHIO.</small>		INTERNATIONAL HYDRAULICS, INC.		
		<b>TITLE: PCB COLLAR AWG 6-18 CONNECTOR W/PRINTED CIRCUIT BOARD TAB</b>		
GENERAL TOLERANCES ±.015 (±0.038)		SCALE: <b>3:1</b>	DRAWN BY: <b>TDS</b>	DWG NO.: B6A-PCB-(SALES)
MATERIAL: <b>6061-T6 (13521)</b>	FINISH: <b>SEE NOTE</b>	DATE: <b>12/04/08</b>	REV:	THIS IS A CAD DRAWING, DO NOT MANUALLY REVISE